

GT-D1M (HR) DOOR TYPE

ECO POWER. PRO PERFORMANCE.




POWER

POWERFUL washing standards. Sustained pressure to deliver extraordinary results. Selectable wash timing. Stainless steel impellers housing.



DURABLE

Stainless steel chamber build. Built from industrial grade 304 stainless steel. ENDURING performance with zero-trouble experience.




DYNAMIC

Electrical components are resistant against the extreme environment and kitchen settings it is put into. It delivers CONSISTENT results everywhere.



HEAT RECOVERY

Incredibly Power Efficient. HUGE power savings, -80% from the Standard Booster Tank heating power. Major heating power comes for excess thermal energy from free steam.



TECHNICAL DATA

Model:	GT-D1M (HR)
Dimensions (mm):	697 (W) x 690 (D) x 1585 (H)
Loading height (mm):	420
Rack type (mm):	500 x 500
Machine net weight	135 kg

OPERATING INFORMATION

Wash temperature:	55°C - 65°C
Rinse temperature:	82°C - 90°C
Wash cycle (per rack):	70/100 seconds (selectable)
Wash rate (per hour):	50/36 racks for 1 phase models
Rinse usage:	<2.0 liters per cycle
Wash tank capacity:	36.0 liters
Booster tank capacity:	10.0 liters
Chemical dispensers:	Optional fitting (sold separately)

ELECTRICAL SPECIFICATIONS

Voltage supply	Booster tank	Wash tank	Wash pump	Total power loading
220V - 240V, 50/60Hz, 1 Phase	2.0 kW	2.0 kW	0.9 kW	3.5 kW, 15.0 A (Alternative Heating) 5.5 kW, 24.0 A (Full Heating)

